


ITEM NO.	PART NUMBER	DESCRIPTION	EXPLODED VIEW/QTY.
1	95410	CAPSCREW SOC HD. M10 x 25	1
2	95411	O-RING, 1.234 ID x .139 WD	1
3	95412	CONNECTOR, MALE 3/8 NPT TO 3/8 TUBE (PARKER# 6-6-FTX-5)	1
4	95420	NOZZLE, 1/4 NPT, 60 DEG FULL CONE, LOW FLOW (BETE# WL-1)	1
5	254938	NOZZLE HOLDER 1/4 NPT, TILT 60 DEG	1
6	254939	WASHER - SPECIAL, FLANGED (M10)	1



NOTES:

**Tapered Thread Port Assembly:**  
 APPLY SEALANT, HAND TIGHTEN, AND THEN WRENCH TIGHTEN PER PARKER ASSEMBLY / INSTALLATION PROCEDURES, CATALOG 4300, P. T7

REV	CHANGED FROM	BY	DATE	APRD
A	PRE-RELEASE	CPS	4/16/13	
B	RELEASE FOR PRODUCTION	CPS	5/13/13	

REPORT ERRORS & CHANGES  
 REMOVE ALL BURRS AND SHARP EDGES  
 DIMENSIONS ARE IN MILLIMETERS.  
 UNSPECIFIED TOLERANCES:  
 DECIMALS: FINISH: ANGLES:

X: ±1.0  
 .X: ±0.5  
 .XX: ±0.25

6.3  $\sqrt{\mu\text{m Ra}}$   $\leq \pm 0.5^\circ$

COPYRIGHT ©

NOT TO BE REPRODUCED OR USED TO MAKE  
 OTHER DRAWINGS OR MACHINERY

DRAWN: CPS DATE: 4/16/13  
 CHECKED: NJB THIRD ANGLE PROJ

**National Renewable Energy Laboratory**

TITLE: NOZZLE ASS'Y: 2nd STAGE: 1/4 NPT TILTED FULL CONE (WL STYLE)

SIZE: **B** DWG. NO. 254937 REV: **B**

SCALE: 1:5 WEIGHT: 22.53 kgs SHEET 1 OF 1