



# COMMERCIAL PRODUCT SPECIFICATION

PART # <b>93239</b>		NAME <b>SEAL, O-RING, 1060mm ID x 8.0mm X-SEC</b>			EST. WEIGHT, Kg <b>0.1</b>	
QUALITY SYSTEM LEVEL <input checked="" type="checkbox"/> N/A <input type="checkbox"/> SOURCE INSPECTION <input type="checkbox"/> FIRST ARTICLE <input type="checkbox"/> INCOMING SAMPLE		BOM FIRST USED FOR <b>ROMAX</b>	PREPARED BY <b>PEI</b>	DATE <b>4/22/13</b>	APPROVAL LEVEL <b>PROCUREMENT</b>	
DOCUMENTS REQUIRED		REVISIONS				
NUMBER	DESCRIPTION	REVISION	NO.	BY	DATE	DESCRIPTION
			A	PEI	4/22/13	RELEASED
DESCRIPTION						
SEAL, O-RING, 1060mm ID x 8.0mm X-SEC PARKER # SPLICED O-RING METHOD - NO TOOLING REQ'D Material: Buna-N						
<b>SOURCE</b>  Parker Hannifin Corp. O-Ring Division 2560 Palumbo Drive, Lexington, KY 40509 P - 859.269.2351 F - 859.335.5128 <a href="http://www.parker.com/o-ring">www.parker.com/o-ring</a>						